


Model: CUZCO TERRA
Codes: 100363498
Group: G-227
Format: 20X23,2X0,85CM



RECOMMENDATIONS		
Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
Recommended joint	100353483 COLORSTUK RAPID ASH N 5KG	
Recommended joint (wet area)	100353483 COLORSTUK RAPID ASH N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	

DIMENSIONAL FEATURES		
Length and width deviation	0.5 %	UNE-EN ISO 10545-2*
Side straightness deviation	0.5 %	UNE-EN ISO 10545-2*
Orthogonality deviation	0.5 %	UNE-EN ISO 10545-2*
Surface flatness deviation	0.5 %	UNE-EN ISO 10545-2*

FEATURES	
 Gloss-free	 Material suitable for use on shower walls.
 Material suitable for use on outdoor walls.	 Material suitable for use on indoor walls.
 Material suitable for use on indoor floors.	 Material recommended for installation on the floor.

PHYSICAL PROPERTIES		
Water absorption	Bla	UNE-EN ISO 10545-3*
Breaking strength	4142.9 N	>1300 N*
Resistance to thermal shock	RESISTE	UNE-EN ISO 10545-9*
Crack resistance	RESISTE 3 CICLOS	UNE-EN ISO 10545-11*
Flammability	A1; A1fl	EN 13501-1*
Slip resistance (wet pendulum) irhd 55	22 (CL1)	UNE-EN 16165 Anexo C*
Dynamic coefficient of friction (dcof)	0.67	ANSI A326.3*
Abrasion resistance	PEI 3	UNE-EN ISO 10545-7*

CHEMICAL PROPERTIES		
Stain resistance	Clase 5	UNE-EN ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	UNE-EN ISO 10545-13*



PACKING		
Sales units per box	0.9022 M2/BOX	
Sales units per pallet	54.132 M2/PAL	
Sales units per unit	0.0347 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	17.809798 KG/M2	
Gross weight	18.184438 KG/M2	

