


Model: PIGMENTS GREY
Codes: 100371119
Group: G-226
Format: 29,7X29,7X0,85CM



RECOMMENDATIONS

Recommended adhesive	100043280 TIXOCEM PLUS 25KG
Recommended joint	100236834 COLORSTUK RAPID GRIS N 5KG
Recommended joint (wet area)	100236834 COLORSTUK RAPID GRIS N 5KG
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG

FEATURES

- 

Gloss-free
- 

Material suitable for use on outdoor walls.
- 

Material suitable for use on indoor floors.
- 

Material suitable for use on shower walls.
- 

Material suitable for use on indoor walls.
- 

Material recommended for installation on the floor.

DIMENSIONAL FEATURES

Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.5 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

PHYSICAL PROPERTIES

Water absorption	Bla	ISO 10545-3*
Breaking strength	1898.0 N	>1300 N*
Resistance to thermal shock	PASS	ISO 10545-9*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1f I/A1	EN 13501-1*
Flexural strength	>51 N/mm2	ISO 10545-4*
Slip resistance (wet pendulum) irhd 55	CLASE 1	UNE EN 16165*
Slip resistance (pendulum-dry)	>40*	
Dynamic coefficient of friction (dcof)	0.72 (T1C1K)	
Abrasion resistance	PEI 3	ISO 10545-7*
Slip resistance (wet pendulum) (aus) irhd 55	19 (T1C1K)	
Slip resistance (wet pendulum) (aus) irhd 96	29 (T1C1K)	



PACKING		
Sales units per box	0.970299 M2/BOX	
Sales units per pallet	46.574352 M2/PAL	
Sales units per unit	0.088209 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	19.555828 KG/M2	
Gross weight	20.020633 KG/M2	

CHEMICAL PROPERTIES		
Stain resistance	CL 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*

