

Model: AREZZO STONE
Codes: 100321869
Group: G-228
Format: 8X30X0,85CM



RECOMMENDATIONS		
Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
Recommended joint	100236449 COLORSTUK RAPID CEMENTO N 5KG	
Recommended joint (wet area)	100236449 COLORSTUK RAPID CEMENTO N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	

DIMENSIONAL FEATURES		
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.3 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

FEATURES		
 Gloss-free	 Material suitable for use on shower walls.	
 Material suitable for use on indoor walls.	 Material recommended for installation on walls.	

PHYSICAL PROPERTIES		
Water absorption	BIII	ISO 10545-2*
Breaking strength	>900 N	>600 N*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1	EN 13501-1*
Flexural strength	>20 MPA	ISO 10545-4*

CHEMICAL PROPERTIES		
Stain resistance	Clase 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*

PACKING		
Sales units per box	0.672 M2/BOX	
Sales units per pallet	67.2 M2/PAL	
Sales units per unit	0.024 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	14.083333 KG/M2	
Gross weight	14.458333 KG/M2	

