

Model: FIJI GREY  
Codes: 100336747  
Group: G-226  
Format: 10X20X0,85CM



| RECOMMENDATIONS                 |                                         |  |
|---------------------------------|-----------------------------------------|--|
| Recommended adhesive            | 100043280 TIXOCEM PLUS 25KG             |  |
| Recommended joint               | 100236449 COLORSTUK RAPID CEMENTO N 5KG |  |
| Recommended joint (wet area)    | 100236449 COLORSTUK RAPID CEMENTO N 5KG |  |
| Recommended adhesive (wet area) | 100043280 TIXOCEM PLUS 25KG             |  |

| DIMENSIONAL FEATURES        |        |                     |
|-----------------------------|--------|---------------------|
| Length and width deviation  | ±0.5%  | UNE-EN ISO 10545-2* |
| Side straightness deviation | ±0.3 % | UNE-EN ISO 10545-2* |
| Orthogonality deviation     | ±0.5%  | UNE-EN ISO 10545-2* |
| Surface flatness deviation  | ±0.5 % | UNE-EN ISO 10545-2* |

| FEATURES                                                                                                                                           |                                                                                                                                     |
|----------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
|  Material with surface with the ability to produce reflections. |  Material suitable for use on shower walls.      |
|  Material suitable for use on indoor walls.                     |  Material recommended for installation on walls. |

| PHYSICAL PROPERTIES                     |                 |               |
|-----------------------------------------|-----------------|---------------|
| Water absorption                        | BIII            | ISO 10545-2*  |
| Breaking strength                       | >900 N          | >600 N*       |
| Coefficient of linear thermal expansion | <6.6 1/(10E6*K) | ISO 10545-8*  |
| Crack resistance                        | PASS            | ISO 10545-11* |
| Flammability                            | A1              | EN 13501-1*   |
| Flexural strength                       | >20 MPA         | ISO 10545-4*  |

| CHEMICAL PROPERTIES     |            |               |
|-------------------------|------------|---------------|
| Stain resistance        | Clase 5    | ISO 10545-14* |
| Resistance to chemicals | GA/GLA/GHA | ISO 10545-13* |



| PACKING                |               |  |
|------------------------|---------------|--|
| Sales units per box    | 0.96 M2/BOX   |  |
| Sales units per pallet | 57.6 M2/PAL   |  |
| Sales units per unit   | 0.02 M2/PIECE |  |
| Sale unit              | M2            |  |
| Base unit              | ST            |  |
| Net weight             | 15.6 KG/M2    |  |
| Gross weight           | 16 KG/M2      |  |

