

Model: DORCIA MARFIL ANT.L 59,6X120(A)

Codes: 100355170

Water absorption: Bla - Porcelanico ( $E \leq 0.1\%$ )

Finish: Non-slip

Tone variations: V2

Rectified: Yes



## DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

Width	596 mm	
Length	1200 mm	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*

\*ISO-13006:2018 UNE-EN 14411:2016

## FEATURES

Surface texture that minimizes the risk of slipping. Soft finishes for safe walking. General deshaded design with a degree of color and appearance variation.

Name given to the finish of those tiles dimensionally improved after the firing process.

## MECHANICAL FEATURES

UNE-EN ISO 10545-4-6-7-11

Crazing resistance	Resists 3 cycles	
--------------------	------------------	--

\*ISO-13006:2018 UNE-EN 14411:2016

## HYGIENIC FEATURES

UNE-EN ISO 10545-13-14:1995

Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*

\*ISO-13006:2018 UNE-EN 14411:2016

## ANTI-SLIP VALUE

EN 16165: 2022 / ANSI 137

Slip resistance (wet pendulum) irhd 55	CL3	
--	-----	--

\*ISO-13006:2018 UNE-EN 14411:2016

## PACKING

Sales units per box	1.430411 M2/BOX	
Sales units per pallet	50.064368 M2/PAL	
Sales units per unit	0.715205 M2/PIECE	

System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double gluing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.

## RECOMMENDED USE LOCATIONS

### Various

Cladding of bonded or mixed facades

Facade cladding with mechanical anchors

### System Certification

