

Model: PARMA DECO LIMESTONE

Codes: 100341495

Group: G-222

Format: 30X30X0,85CM



RECOMMENDATIONS		
Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
Recommended joint	100236808 COLORSTUK RAPID BEIGE N 5KG	
Recommended joint (wet area)	100236808 COLORSTUK RAPID BEIGE N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	

DIMENSIONAL FEATURES		
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.5 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

FEATURES	
 Gloss-free	 Material suitable for use on shower walls.
 Material suitable for use on outdoor walls.	 Material suitable for use on indoor walls.
 Material suitable for use on indoor floors.	 Material recommended for installation on the floor.

PHYSICAL PROPERTIES		
Water absorption	Bla	ISO 10545-3*
Breaking strength	>2100 N	>1300 N*
Resistance to thermal shock	PASS	UNE-EN ISO 10545-9*
Crack resistance	PASS	UNE-EN ISO 10545-11*
Flammability	A1f I/A1	EN 13501-1*
Slip resistance (wet pendulum) irhd 55	CL 1 (35)	EN 16165 Anexo C*
Slip resistance (pendulum-dry)	90	
Dynamic coefficient of friction (dcof)	0.44	
Abrasion resistance	PEI 3	

CHEMICAL PROPERTIES		
Stain resistance	CL 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*



PACKING		
Sales units per box	0.99 M2/BOX	
Sales units per pallet	47.52 M2/PAL	
Sales units per unit	0.09 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	18.922222 KG/M2	
Gross weight	19.411111 KG/M2	

