

Model: HERITAGE MADRID
Codes: 100336820
Group: G-226
Format: 20X20X0,85CM



RECOMMENDATIONS		
Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
Recommended joint	100236449 COLORSTUK RAPID CEMENTO N 5KG	
Recommended joint (wet area)	100236449 COLORSTUK RAPID CEMENTO N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	

DIMENSIONAL FEATURES		
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.5 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

FEATURES	
 Gloss-free	 Material suitable for use on shower walls.
 Material suitable for use on outdoor walls.	 Material suitable for use on indoor walls.
 Material suitable for use on indoor floors.	 Material recommended for installation on the floor.

PHYSICAL PROPERTIES		
Water absorption	Bla	ISO 10545-3*
Breaking strength	2635.5 N	>1300 N*
Coefficient of linear thermal expansion	<6.6 1/(10E6*K)	
Resistance to thermal shock	PASS	ISO 10545-9*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1f I/A1	EN 13501-1*
Flexural strength	>51 MPA	ISO 10545-4*
Slip resistance (wet pendulum) irhd 55	CL 1 (28)	EN 16165 Anexo C*
Slip resistance (shod feet)	R9	EN 16165 Anexo B*
Slip resistance (pendulum-dry)	80	
Dynamic coefficient of friction (dcof)	0.74 (T5C1K)	
Abrasion resistance	PEI 3 / 600v	
Slip resistance (wet pendulum) (aus) irhd 55	P2	AS 4586*
Slip resistance (wet pendulum) (aus) irhd 96	P3	AS 4586*



CHEMICAL PROPERTIES		
Stain resistance	CL 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*

PACKING		
Sales units per box	0.88 M2/BOX	
Sales units per pallet	52.8 M2/PAL	
Sales units per unit	0.04 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	20.225 KG/M2	
Gross weight	20.65 KG/M2	

