

Model: MARMOL CARRARA BLANCO 33,3X100(A)

Codes: 100291740

Water absorption: BIII - Cladding Tile ( $10.0\% < w_a \leq 20.0\%$ )

Finish: Glazed / Standard

Tone variations: V2

Rectified: Yes



## DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

|                             |             |          |
|-----------------------------|-------------|----------|
| Thickness                   | 9.3 mm      | +/-5%*   |
| Width                       | 332.8 mm    |          |
| Length                      | 1000 mm     |          |
| Length and width deviation  | Below 0.15% | +/-0.3%* |
| Side straightness deviation | Below 0.15% | +/-0.3%* |
| Squareness deviation        | Below 0.15% | +/-0.3%* |
| Surface flatness deviation  | Below 0.15% | +/-0.4%* |

\*ISO-13006:2018 UNE-EN 14411:2016

## FEATURES



Glossy surface finish with a high degree of light reflection.



Name given to the finish of those tiles dimensionally improved after the firing process.



Wall installation

## MECHANICAL FEATURES

UNE-EN ISO 10545-4-6-7-9-11

|                    |                       |                          |
|--------------------|-----------------------|--------------------------|
| Breaking strength  | >1100 N               | >600 N*                  |
| Modulus of rupture | >23 N/mm <sup>2</sup> | >=12 N/mm <sup>2</sup> * |
| Crazing resistance | PASS                  |                          |

\*ISO-13006:2018 UNE-EN 14411:2016

## HYGIENIC FEATURES

UNE-EN ISO 10545-13-14

|                     |                                                                                                            |         |
|---------------------|------------------------------------------------------------------------------------------------------------|---------|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* |
| Stain resistance    | Class 5. Easy cleaning with water                                                                          | 3 Min.* |

\*ISO-13006:2018 UNE-EN 14411:2016

## DETERMINATION OF LIGHT REFLECTANCE VALUE (LRV)

UNE-EN ISO 10545-18

|                                                |       |  |
|------------------------------------------------|-------|--|
| Determination of light reflectance value (Irv) | 86.22 |  |
|------------------------------------------------|-------|--|

\*ISO-13006:2018 UNE-EN 14411:2016

System Certification



## PACKING

|                        |                  |  |
|------------------------|------------------|--|
| Sales units per box    | 1.665002 M2/BOX  |  |
| Sales units per pallet | 73.260073 M2/PAL |  |
| Sales units per unit   | 0.333 M2/PIECE   |  |

## SCOPE OF USE

|                  |                  |  |
|------------------|------------------|--|
| Technical code-1 | 1 - Use on walls |  |
|------------------|------------------|--|

## System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.