


Model: PIGMENTS HONEY
Codes: 100371125
Group: G-226
Format: 14,7X14,7X0,85CM



RECOMMENDATIONS		
Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
Recommended joint	100236794 COLORSTUK RAPID MARFIL N 5KG	
Recommended joint (wet area)	100236794 COLORSTUK RAPID MARFIL N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	

DIMENSIONAL FEATURES		
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.5 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

FEATURES		
 Gloss-free	 Material suitable for use on shower walls.	
 Material suitable for use on outdoor walls.	 Material suitable for use on indoor walls.	
 Material suitable for use on indoor floors.	 Material recommended for installation on the floor.	

PHYSICAL PROPERTIES		
Water absorption	Bla	ISO 10545-3*
Breaking strength	2387.8 N	>1300 N*
Resistance to thermal shock	PASS	ISO 10545-9*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1f I/A1	EN 13501-1*
Flexural strength	>51 N/mm2	ISO 10545-4*
Slip resistance (wet pendulum) irhd 55	CLASE 1	UNE EN 16165*
Slip resistance (pendulum-dry)	>40*	
Dynamic coefficient of friction (dcof)	0.68 (T1C1K)	
Abrasion resistance	PEI 3	ISO 10545-7*
Slip resistance (wet pendulum) (aus) irhd 55	26 (T1C1K)	
Slip resistance (wet pendulum) (aus) irhd 96	35 (T1C1K)	

CHEMICAL PROPERTIES		
Stain resistance	CL 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*



PACKING		
Sales units per box	0.302526 M2/BOX	
Sales units per pallet	54.454665 M2/PAL	
Sales units per unit	0.021609 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	19.991676 KG/M2	
Gross weight	20.685831 KG/M2	

