

Model: CUZCO CONCRETE  
Codes: 100363670  
Group: G-227  
Format: 20X23,2X0,85CM



| RECOMMENDATIONS                 |                                           |  |
|---------------------------------|-------------------------------------------|--|
| Recommended adhesive            | 100043280 TIXOCEM PLUS 25KG               |  |
| Recommended joint               | 100236481 COLORSTUK RAPID ANTRACITA N 5KG |  |
| Recommended joint (wet area)    | 100236481 COLORSTUK RAPID ANTRACITA N 5KG |  |
| Recommended adhesive (wet area) | 100043280 TIXOCEM PLUS 25KG               |  |

| DIMENSIONAL FEATURES        |       |                     |
|-----------------------------|-------|---------------------|
| Length and width deviation  | 0.5 % | UNE-EN ISO 10545-2* |
| Side straightness deviation | 0.5 % | UNE-EN ISO 10545-2* |
| Orthogonality deviation     | 0.5 % | UNE-EN ISO 10545-2* |
| Surface flatness deviation  | 0.5 % | UNE-EN ISO 10545-2* |

| FEATURES                                                                                                                        |                                                                                                                                         |
|---------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
|  Gloss-free                                  |  Material suitable for use on shower walls.          |
|  Material suitable for use on outdoor walls. |  Material suitable for use on indoor walls.          |
|  Material suitable for use on indoor floors. |  Material recommended for installation on the floor. |

| PHYSICAL PROPERTIES                    |                  |                       |
|----------------------------------------|------------------|-----------------------|
| Water absorption                       | Bla              | UNE-EN ISO 10545-3*   |
| Breaking strength                      | 4225.5 N         | >1300 N*              |
| Resistance to thermal shock            | RESISTE          | UNE-EN ISO 10545-9*   |
| Crack resistance                       | RESISTE 3 CICLOS | UNE-EN ISO 10545-11*  |
| Flammability                           | A1; A1fl         | EN 13501-1*           |
| Slip resistance (wet pendulum) irhd 55 | 20 (CL1)         | UNE-EN 16165 Anexo C* |
| Dynamic coefficient of friction (dcof) | 0.68             | ANSI A326.3*          |
| Abrasion resistance                    | PEI 2            | UNE-EN ISO 10545-7*   |

| CHEMICAL PROPERTIES     |            |                      |
|-------------------------|------------|----------------------|
| Stain resistance        | Clase 5    | UNE-EN ISO 10545-14* |
| Resistance to chemicals | GA/GLA/GHA | UNE-EN ISO 10545-13* |



| PACKING                |                 |  |
|------------------------|-----------------|--|
| Sales units per box    | 0.9022 M2/BOX   |  |
| Sales units per pallet | 54.132 M2/PAL   |  |
| Sales units per unit   | 0.0347 M2/PIECE |  |
| Sale unit              | M2              |  |
| Base unit              | ST              |  |
| Net weight             | 17.809798 KG/M2 |  |
| Gross weight           | 18.184438 KG/M2 |  |

