

Model: HERITAGE GREY  
Codes: 100336813  
Group: G-226  
Format: 20X20X0,85CM



| RECOMMENDATIONS                 |                                         |  |
|---------------------------------|-----------------------------------------|--|
| Recommended adhesive            | 100043280 TIXOCEM PLUS 25KG             |  |
| Recommended joint               | 100236449 COLORSTUK RAPID CEMENTO N 5KG |  |
| Recommended joint (wet area)    | 100236449 COLORSTUK RAPID CEMENTO N 5KG |  |
| Recommended adhesive (wet area) | 100043280 TIXOCEM PLUS 25KG             |  |

| DIMENSIONAL FEATURES        |        |                     |
|-----------------------------|--------|---------------------|
| Length and width deviation  | ±0.5%  | UNE-EN ISO 10545-2* |
| Side straightness deviation | ±0.5 % | UNE-EN ISO 10545-2* |
| Orthogonality deviation     | ±0.5%  | UNE-EN ISO 10545-2* |
| Surface flatness deviation  | ±0.5 % | UNE-EN ISO 10545-2* |

| FEATURES                                                                                                                        |                                                                                                                                         |
|---------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
|  Gloss-free                                  |  Material suitable for use on shower walls.          |
|  Material suitable for use on outdoor walls. |  Material suitable for use on indoor walls.          |
|  Material suitable for use on indoor floors. |  Material recommended for installation on the floor. |

| PHYSICAL PROPERTIES                          |              |                   |
|----------------------------------------------|--------------|-------------------|
| Water absorption                             | Bla          | ISO 10545-3*      |
| Breaking strength                            | >2100 N      | >1300 N*          |
| Resistance to thermal shock                  | PASS         | ISO 10545-9*      |
| Crack resistance                             | PASS         | ISO 10545-11*     |
| Flammability                                 | A1f I/A1     | EN 13501-1*       |
| Flexural strength                            | >51 MPA      | ISO 10545-4*      |
| Slip resistance (wet pendulum) irhd 55       | CL 1 (28)    | EN 16165 Anexo C* |
| Slip resistance (shod feet)                  | R9           | EN 16165 Anexo B* |
| Slip resistance (pendulum-dry)               | 80           |                   |
| Dynamic coefficient of friction (dcof)       | 0.80 (T3C1K) |                   |
| Abrasion resistance                          | PEI 3        |                   |
| Slip resistance (wet pendulum) (aus) irhd 55 | P3           | AS 4586*          |
| Slip resistance (wet pendulum) (aus) irhd 96 | P4           | AS 4586*          |



| CHEMICAL PROPERTIES     |               |               |
|-------------------------|---------------|---------------|
| Stain resistance        | CL 5          | ISO 10545-14* |
| Resistance to chemicals | GA/GLA/GHA    | ISO 10545-13* |
| PACKING                 |               |               |
| Sales units per box     | 0.88 M2/BOX   |               |
| Sales units per pallet  | 52.8 M2/PAL   |               |
| Sales units per unit    | 0.04 M2/PIECE |               |
| Sale unit               | M2            |               |
| Base unit               | ST            |               |
| Net weight              | 20.15 KG/M2   |               |
| Gross weight            | 20.55 KG/M2   |               |



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.