

Model: PIGMENTS ASH
Codes: 100370947
Group: G-226
Format: 14,7X29,7X0,85CM



RECOMMENDATIONS		
Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
Recommended joint	100353483 COLORSTUK RAPID ASH N 5KG	
Recommended joint (wet area)	100353483 COLORSTUK RAPID ASH N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	

DIMENSIONAL FEATURES		
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.5 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

FEATURES		
 Gloss-free	 Material suitable for use on shower walls.	
 Material suitable for use on outdoor walls.	 Material suitable for use on indoor walls.	
 Material suitable for use on indoor floors.	 Material recommended for installation on the floor.	

PHYSICAL PROPERTIES		
Water absorption	Bla	ISO 10545-3*
Breaking strength	2291.6 N	>1300 N*
Resistance to thermal shock	PASS	ISO 10545-9*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1f I/A1	EN 13501-1*
Flexural strength	>51 N/mm2	ISO 10545-4*
Slip resistance (wet pendulum) irhd 55	CLASE 1	UNE EN 16165*
Slip resistance (pendulum-dry)	>40*	
Dynamic coefficient of friction (dcof)	0.69 (T1C1K)	
Abrasion resistance	PEI 3	ISO 10545-7*
Slip resistance (wet pendulum) (aus) irhd 55	20 (T1C1K)	
Slip resistance (wet pendulum) (aus) irhd 96	33 (T1C1K)	

CHEMICAL PROPERTIES		
Stain resistance	CL 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*



PACKING		
Sales units per box	0.611226 M2/BOX	
Sales units per pallet	46.453174 M2/PAL	
Sales units per unit	0.043659 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	19.675211 KG/M2	
Gross weight	20.133307 KG/M2	

