

Model: SAILS CREAM
Codes: 100371649
Group: G-226
Format: 16X16X0,95CM



RECOMMENDATIONS		
Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
Recommended joint	100236808 COLORSTUK RAPID BEIGE N 5KG	
Recommended joint (wet area)	100236808 COLORSTUK RAPID BEIGE N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	

DIMENSIONAL FEATURES		
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.3 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

FEATURES	
 Material with surface with the ability to produce reflections.	 Material suitable for use on shower walls.
 Material suitable for use on indoor walls.	 Material that features unevenness on the surface.
 Material recommended for installation on walls.	

PHYSICAL PROPERTIES		
Water absorption	BIII	ISO 10545-2*
Breaking strength	>900 N	>600 N*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1	EN 13501-1*

CHEMICAL PROPERTIES		
Stain resistance	Clase 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*



PACKING		
Sales units per box	0.5376 M2/BOX	
Sales units per pallet	64.512 M2/PAL	
Sales units per unit	0.0256 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	15.15625 KG/M2	
Gross weight	15.507812 KG/M2	

