

Model: SAVOYA DUN
Codes: 100226668
Group: G-125
Format: 29,7X32,2X0,9CM



RECOMMENDATIONS		
Recommended adhesive	100201526 ONE-FLEX PREMIUM BLANCO 25KG	
Recommended joint	100236481 COLORSTUK RAPID ANTRACITA N 5KG	
Recommended joint (wet area)	100236481 COLORSTUK RAPID ANTRACITA N 5KG	100086920 FILA FOB XTREME 1L
Recommended adhesive (wet area)	100201526 ONE-FLEX PREMIUM BLANCO 25KG	

TECHNICAL INFORMATION		
Slip resistance (wet pendulum) irhd 55	CL 1 (20)	EN 16165 Anexo C*
Slip resistance (pendulum-dry)	70	
Dynamic coefficient of friction (dcof)	0.49	ANSI 137.1*
Composition	SLATE/GLAZED CERAMICS	

FEATURES	
 Product manufactured on a mesh that makes installation easier.	 Material with surface with the ability to produce reflections.
 Material suitable for use on shower floors.	 Material suitable for use on shower walls.
 Material suitable for use on indoor walls.	

PACKING		
Sales units per square meter	10.456533 PIECES/M2	
Sales units per box	11 PIECES/BOX	
Sales units per unit	1 PIECES	
Sale unit	ST	
Base unit	ST	
Net weight	1.5 KG/PIECES	
Gross weight	1.547 KG/PIECES	

